

Firebird® Heavy Duty EC Diesel Engine Oil

Phillips 66[®] Firebird Heavy Duty EC (Emission Compatible) Diesel Engine Oil is an environmentally responsible API CK-4 engine oil developed for use in four-stroke cycle diesel engines designed to meet 2007 and later EPA on-highway exhaust emissions standards. It is specially formulated for compatibility with exhaust aftertreatment systems using diesel particulate filters (DPFs), diesel oxidation catalysts (DOCs) and/or selective catalytic reduction (SCR). It is backward serviceable for use in pre-2007 diesel engines.

Firebird Heavy Duty EC is formulated with 100% re-refined base stocks. It has excellent soot dispersancy to protect against soot-induced oil thickening and abrasive wear, and excellent oxidation resistance to help minimize deposit formation. The low-ash formulation protects exhaust catalysts on low-emission engines and helps prolong DPF life. The use of re-refined base stocks helps lessen the environmental impact of disposal of used oil.

Firebird Heavy Duty EC meets or exceeds the performance requirements of API Service Category CK-4 and SN as well as leading OEM specifications for use in low-emission diesel engines. It is backward serviceable for use where earlier API "C" category engine oils, or the concurrent earlier OEM specifications, are specified. It is formulated for use in diesel engines operating on diesel fuels with sulfur content up to 500 ppm. However, for applications not using Ultra-Low Sulfur Diesel (ULSD), consult the engine manufacturer for recommended service interval.

Applications

- On-highway diesel trucks equipped with EGR and exhaust aftertreatment systems to meet 2007/2010 emissions standards
- Older diesel equipment with conventional, non-EGR engines or ACERT engines
- Off-highway construction, earth moving and mining equipment

Firebird Heavy Duty EC is licensed or OEM-certified for:

- API Service CK-4, CJ-4, CI-4 PLUS, SN
- Cummins CES 20086
- Detroit Diesel DFS 93K222
- Ford WSS-M2C171-F1

Firebird Heavy Duty EC meets or exceeds the requirements of:

- Caterpillar ECF-3, ECF-2, ECF-1-a
- Mack EOS 4.5
- Mercedes-Benz Sheet 228.31
- Volvo VDS-4.5

API CK-4 Diesel Engine Oil Formulated with Re-refined Base Stocks



U.S. Customer Service: 1-800-368-7128 Technical Hotline: 1-877-445-9198 International Customer Service: 1-832-765-2500

E-mail address: phillips66lubricants@p66.com



- Diesel engines manufactured by OEMs not listed above, where the OEM specifies API CK-4 engine oil

Features/Benefits

- Excellent protection for newer low-emission diesel engines and older diesel engines
- Specially formulated to protect exhaust aftertreatment systems
- Protects against particulate filter plugging
- · Excellent soot control for protection against abrasive wear and soot-induced oil thickening
- Excellent resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge and varnish formation
- Protects against rust, bearing corrosion and wear
- · Good resistance to foaming and aeration
- Lessens the environmental impact of used oil disposal

Firebird[®] Heavy Duty EC Diesel Engine Oil

Typical Properties	
SAE Grade	15W-40
Specific Gravity @ 60°F	0.8774
Density, Ibs/gal @ 60°F	7.31
Color, ASTM D1500	L 4.0
Flash Point (COC), °C (°F)	235 (455)
Pour Point, °C (°F)	-31 (-24)
Viscosity, Kinematic	
cSt @ 40°C	111
cSt @ 100°C	15.0
Viscosity Index	139
Cold Cranking Viscosity, cP @ -20°C	5,400
High-Temp/High-Shear Viscosity, cP @ 150°C	4.2
Sulfated Ash, ASTM D874, wt %	0.99
Total Base Number (TBN), ASTM D2896	9.7
Zinc, wt %	0.1250
Re-refined Content, Base Oil, vol %	100

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <u>http://www.phillips66.com/EN/products/Pages/MSDS.aspx</u>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© Phillips 66 Company. Phillips 66[®] and its respective logos and products are registered trademarks of Phillips 66 Company in the U.S.A. and other countries.