



LUBRICANTS

## Triton® Arctic Diesel Engine Oil

Phillips 66® Triton Arctic Diesel Engine Oil is a premium quality, full-synthetic engine oil developed for use in 4-stroke cycle diesel engines operating under arctic temperature conditions. It meets API CK-4 performance requirements for use in modern low-emission engines designed to meet 2007 and later EPA on-highway exhaust emissions standards, and is backward serviceable for use in older diesel engines. It is specially formulated for compatibility with exhaust aftertreatment systems using diesel particulate filters (DPF), diesel oxidation catalysts (DOC) and/or selective catalytic reduction (SCR). The full-synthetic formulation and SAE 0W-40 viscosity grade provide excellent low-temperature properties for better performance in harsh arctic climates.

Triton Arctic Diesel Engine Oil is formulated with synthetic base stocks and an advanced low-SAPS additive package to provide outstanding wear protection, soot control and bearing corrosion protection in both conventional and EGR-equipped diesel engines. It has excellent soot dispersancy to protect against abrasive wear and soot-induced oil thickening, and to ensure good low-temperature pumpability even with highly soot-laden oil. The full-synthetic formulation provides enhanced oxidation resistance and thermal stability at high temperatures and improved low-temperature properties compared with a conventional, non-synthetic formulation.

Triton Arctic Diesel Engine Oil is recommended for use in diesel engines where an API CK-4 quality engine oil is specified, and is backward serviceable for use where earlier API "C" category engine oils are specified.

### Applications

- On- and off- highway diesel equipment operating at very low ambient temperatures
- On-highway diesel trucks equipped with EGR and exhaust aftertreatment systems to meet 2007/2010 emissions standards
- Older diesel equipment with conventional, non-EGR engines or ACERT engines
- Off-highway construction, earth moving and mining equipment

Triton Arctic Diesel Engine Oil meets or exceeds the requirements of:

- Diesel engines manufactured by Caterpillar, Cummins, Detroit Diesel, Mack, Mercedes-Benz, Volvo and other OEMs where the OEM specifies an SAE 0W-40, API CK-4 engine oil

**Premium Full-Synthetic Diesel Engine Oil for Arctic Climates; Fortified with Liquid Titanium® Protection Additive**

KEEPING THE  
WORLD  
RUNNING  
SMOOTHLY. 



## Features/Benefits

- Excellent protection for newer low-emission diesel engines and older diesel engines
- Specially formulated to protect exhaust aftertreatment systems
- Outstanding soot control for protection against abrasive wear and soot-induced oil thickening
- Outstanding resistance to viscosity and thermal breakdown at high temperatures
- Exclusive Liquid Titanium additive provides enhanced oxidation and wear control
- Protects against rust, bearing corrosion and wear
- Excellent low-temperature pumpability for easier starting and less wear during cold starts
- High shear stability
- High resistance to foaming and aeration

## Triton<sup>®</sup> Arctic Diesel Engine Oil

Typical Properties	
<b>SAE Grade</b>	<b>0W-40</b>
Specific Gravity @ 60°F	0.846
Density, lbs/gal @ 60°F	7.04
Color, ASTM D1500	4.0
Flash Point (COC), °C (°F)	226 (439)
Pour Point, °C (°F)	-58 (-72)
Viscosity, Kinematic	
cSt @ 40°C	85
cSt @ 100°C	14.4
Viscosity Index	178
Cold Cranking Viscosity, cP @ -35°C	5,853
High-Temp/High-Shear Viscosity, cP @ 150°C	4.0
Sulfated Ash, ASTM D874, wt %	1.0
Total Base Number (TBN), ASTM D2896	10.8
Zinc, wt %	0.1215
Titanium, wt %	0.010

## Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/EN/products/Pages/MSDS.aspx>.

02-05-2018

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© Phillips 66 Company. Phillips 66<sup>®</sup> and its respective logos and products are registered trademarks of Phillips 66 Company in the U.S.A. and other countries.