



LUBRICANTS

Wool Processing Oil

Phillips 66® Wool Processing Oil is a high-quality, low-viscosity mineral oil developed for use as a wool processing oil. It improves cohesion of the wool fibers and helps protect them during processing and spinning the wool into yarn. It also helps reduce static during processing.

Wool Processing Oil has very light color and is non-staining. It is inhibited against oxidation to maintain color stability.

Applications

- Wool Processing Oil

Features/Benefits

- Very light color
- Non-staining
- Good color stability

Light Mineral Oil for Processing & Spinning Wool

KEEPING THE
WORLD
RUNNING
SMOOTHLY.





Wool Processing Oil

Typical Properties	
ISO Grade	22
Specific Gravity @ 60°F	0.853
Density, lbs/gal @ 60°F	7.10
Color, ASTM D1500	0.5
Flash Point (COC), °C (°F)	209 (408)
Pour Point, °C (°F)	-15 (5)
Viscosity	
cSt @ 40°C	22.5
cSt @ 100°C	4.4
SUS @ 100°F	108.5
SUS @ 210°F	40.8
Viscosity Index	102

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/EN/products/Pages/MSDS.aspx>.